



**PAT-NO:** JP363295485A  
**DOCUMENT-IDENTIFIER:** JP 63295485 A  
**TITLE:** MOLDING MATERIAL FOR LIGHTWEIGHT AERATED CONCRETE  
**PUBN-DATE:** December 1, 1988

**INVENTOR-INFORMATION:**

NAME	COUNTRY
INAO, MASAYUKI	
TOMIUCHI, SHINICHI	
KAWADA, AKIO	

**ASSIGNEE-INFORMATION:**

NAME	COUNTRY
MATSUSHITA ELECTRIC WORKS LTD	N/A

**APPL-NO:** JP62130285  
**APPL-DATE:** May 27, 1987

**INT-CL (IPC):** C04B038/10

**ABSTRACT:**

**PURPOSE:** To produce a molding material for lightweight aerated concrete capable of increasing its sound absorption characteristic, etc., by incorporating bubbles foamed with a foaming agent, and deforming agent in a slurry dispersed cement in water to form bubbles having large diameter.

**CONSTITUTION:** The molding material for lightweight aerated concrete is prepared by dispersing cement in water and besides, is combined bubbles foamed using the foaming agent with the defoaming agent. Conventional agent, natural protein such as glue, casein, albumin, and amphoteric surfactant can be used as the foaming agent. silicone defoaming agent is mainly used as the deforming agent but oily material (e.g. higher alcohol, ethylene glycol, etc.,) and nonionic surfactant, etc., can be also used.

**COPYRIGHT:** (C)1988,JPO&Japio